



OUR NAME. OUR REPUTATION. O'MARA.

O'MARA HCR SERIES - HIGH CAPACITY BELT CONVEYOR

Troughed roller, open frame design is ideal for handling high volumes of bulk materials in continuous, severe duty applications that run 24/7.



STANDARD FEATURES



- ✓ Custom designed, sized, and built per your specific requirements in 24" to 48" beltwidths.
- ✓ Shaft mounted drives engineered for each individual application.
- ✓ Dodge series 2000 pillow block roller bearings.
- ✓ Conveyor belting suited to each application. Belting meets requirements for oil resistance, fire resistance, and low static resistivity.
- ✓ Crowned drive pulley lagged with Holtz or equal 3/8" slide lagging.
- ✓ Crowned take-up / tail pulley. Shaft drilled and tapped at both ends for motion sensor.
- ✓ CEMA equal length troughers available in 20, 35, or 45 degree trough angles.
- ✓ Screw take-up frames designed for use with series 2000 pillow block bearings.
- ✓ Heavy duty structural channel, open conveyor frames.
- ✓ Full guarding packages available to meet your safety requirements.
- ✓ Gray powder coat finish, or may coat to your specific color requirements.
- ✓ Many Options available



O'MARA AG & EQUIPMENT SERVICES

1626 Delaware Ave.
Des Moines, IA 50317
(515) 989-2094
www.omara-ag.com

ROBIN O'MARA,

President / (515) 321-5267
romara60@msn.com

BRUCE COCKRAM,

Outside Sales / (515) 681-2160
Bruce.Cockram@omara-ag.com